

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Hexane

Product Number : 296090  
Brand : Sigma-Aldrich

Supplier : Sigma-Aldrich  
3050 Spruce Street  
SAINT LOUIS MO 63103  
USA

Telephone : +1 800-325-5832  
Fax : +1 800-325-5052  
Emergency Phone # (For both supplier and manufacturer) : (314) 776-6555

Preparation Information : Sigma-Aldrich Corporation  
Product Safety - Americas Region  
1-800-521-8956

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

##### OSHA Hazards

Flammable liquid, Target Organ Effect, Irritant

##### Target Organs

Peripheral nervous system., Kidney, Testes.

##### GHS Classification

Flammable liquids (Category 2)  
Skin irritation (Category 2)  
Eye irritation (Category 2B)  
Reproductive toxicity (Category 2)  
Specific target organ toxicity - single exposure (Category 3)  
Specific target organ toxicity - single exposure (Category 2)  
Aspiration hazard (Category 1)  
Acute aquatic toxicity (Category 2)

##### GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 + H320 Causes skin and eye irritation.  
H336 May cause drowsiness or dizziness.  
H361 Suspected of damaging fertility or the unborn child.  
H371 May cause damage to organs.  
H401 Toxic to aquatic life.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P281 Use personal protective equipment as required.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P331 Do NOT induce vomiting.

#### HMIS Classification

Health hazard: 2  
Chronic Health Hazard: \*  
Flammability: 3  
Physical hazards: 0

#### NFPA Rating

Health hazard: 2  
Fire: 3  
Reactivity Hazard: 0

#### Potential Health Effects

**Inhalation** May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause drowsiness and dizziness.  
**Skin** May be harmful if absorbed through skin. Causes skin irritation.  
**Eyes** Causes eye irritation.  
**Ingestion** May be harmful if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage.

---

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : *n*-Hexane  
Formula : C<sub>6</sub>H<sub>14</sub>  
Molecular Weight : 86.18 g/mol

CAS-No.	EC-No.	Index-No.	Concentration
<b>n-Hexane</b>			
110-54-3	203-777-6	601-037-00-0	-

---

### 4. FIRST AID MEASURES

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

---

### 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

#### Special protective equipment for fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

**Hazardous combustion products**

Hazardous decomposition products formed under fire conditions. - Carbon oxides

**Further information**

Use water spray to cool unopened containers.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions**

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

**Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

**Methods and materials for containment and cleaning up**

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

**7. HANDLING AND STORAGE****Precautions for safe handling**

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Flash back possible over considerable distance. Container explosion may occur under fire conditions. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

**Conditions for safe storage**

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Components with workplace control parameters**

Components	CAS-No.	Value	Control parameters	Basis
n-Hexane	110-54-3	TWA	50 ppm 180 mg/m <sup>3</sup>	USA. NIOSH Recommended Exposure Limits
		TWA	50 ppm	USA. ACGIH Threshold Limit Values (TLV)
Remarks	Central Nervous System impairment Eye irritation Peripheral neuropathy Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption			
		TWA	50 ppm 180 mg/m <sup>3</sup>	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	500 ppm 1,800 mg/m <sup>3</sup>	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	The value in mg/m <sup>3</sup> is approximate.			

**Personal protective equipment****Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

**Hand protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

**Eye protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

**Skin and body protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

**Hygiene measures**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

---

**9. PHYSICAL AND CHEMICAL PROPERTIES****Appearance**

Form	liquid
Colour	colourless

**Safety data**

pH	7.0
Melting point/freezing point	Melting point/range: -95 °C (-139 °F)
Boiling point	69 °C (156 °F)
Flash point	-26.0 °C (-14.8 °F) - closed cup
Ignition temperature	234 °C (453 °F)
Autoignition temperature	234.0 °C (453.2 °F)
Lower explosion limit	1.2 %(V)
Upper explosion limit	7.7 %(V)
Vapour pressure	341.3 hPa (256.0 mmHg) at 37.7 °C (99.9 °F) 176.0 hPa (132.0 mmHg) at 20.0 °C (68.0 °F)
Density	0.659 g/mL at 25 °C (77 °F)
Water solubility	insoluble
Partition coefficient: n-octanol/water	log Pow: 3.90 - 4.11
Relative vapour density	no data available
Odour	no data available
Odour Threshold	no data available
Evaporation rate	15.8

---

**10. STABILITY AND REACTIVITY****Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

Vapours may form explosive mixture with air.

**Conditions to avoid**

Exposure to moisture may affect product quality.  
Heat, flames and sparks. Extremes of temperature and direct sunlight.

**Materials to avoid**

Oxidizing agents

**Hazardous decomposition products**

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - no data available

---

**11. TOXICOLOGICAL INFORMATION****Acute toxicity****Oral LD50**

LD50 Oral - rat - 25,000 mg/kg

**Inhalation LC50**

LC50 Inhalation - rat - 4 h - 48000 ppm

**Dermal LD50**

no data available

**Other information on acute toxicity**

no data available

**Skin corrosion/irritation**

no data available

**Serious eye damage/eye irritation**

Eyes - rabbit - Mild eye irritation

**Respiratory or skin sensitization**

no data available

**Germ cell mutagenicity**

no data available

**Carcinogenicity**

Carcinogenicity - rat - Inhalation

Tumorigenic: Carcinogenic by RTECS criteria. Tumorigenic Effects: Testicular tumors.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**Reproductive toxicity**

Overexposure may cause reproductive disorder(s) based on tests with laboratory animals.

**Teratogenicity**

Suspected human reproductive toxicant

**Specific target organ toxicity - single exposure (Globally Harmonized System)**

May cause damage to organs.

May cause drowsiness or dizziness.

**Specific target organ toxicity - repeated exposure (Globally Harmonized System)**

no data available

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Potential health effects**

<b>Inhalation</b>	May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause drowsiness and dizziness.
<b>Ingestion</b>	May be harmful if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage.
<b>Skin</b>	May be harmful if absorbed through skin. Causes skin irritation.
<b>Eyes</b>	Causes eye irritation.

**Signs and Symptoms of Exposure**

Prolonged or repeated contact with skin may cause:., defatting, Dermatitis, Contact with eyes can cause:., Redness, Blurred vision, Provokes tears., Effects due to ingestion may include:., Gastrointestinal discomfort, Central nervous system depression, Lung irritation, chest pain, pulmonary edema, giddiness, slowed reaction time, slurred speech, Headache, Dizziness, Drowsiness, Unconsciousness

**Synergistic effects**

no data available

**Additional Information**

RTECS: MN9275000

---

**12. ECOLOGICAL INFORMATION****Toxicity**

Toxicity to fish	LC50 - Pimephales promelas (fathead minnow) - 2.5 mg/l - 96.0 h
Toxicity to daphnia and other aquatic invertebrates.	EC50 - Daphnia magna (Water flea) - 3,878.00 mg/l - 48 h
Toxicity to algae	EC50 - Chlorella vulgaris (Fresh water algae) - 12,840.00 mg/l - 3 h EC50 - SKELETOMA - 0.30 mg/l - 8 h

**Persistence and degradability**

no data available

**Bioaccumulative potential**

no data available

**Mobility in soil**

no data available

**PBT and vPvB assessment**

no data available

**Other adverse effects**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Toxic to aquatic life.

---

**13. DISPOSAL CONSIDERATIONS****Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

**Contaminated packaging**

Dispose of as unused product.

---

**14. TRANSPORT INFORMATION**

**DOT (US)**

UN number: 1208 Class: 3 Packing group: II  
Proper shipping name: Hexanes  
Reportable Quantity (RQ): 5000 lbs  
Marine pollutant: No  
Poison Inhalation Hazard: No

**IMDG**

UN number: 1208 Class: 3 Packing group: II EMS-No: F-E, S-D  
Proper shipping name: HEXANES  
Marine pollutant: No

**IATA**

UN number: 1208 Class: 3 Packing group: II  
Proper shipping name: Hexanes

---

**15. REGULATORY INFORMATION****OSHA Hazards**

Flammable liquid, Target Organ Effect, Irritant

**SARA 302 Components**

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313 Components**

	CAS-No.	Revision Date
n-Hexane	110-54-3	2007-07-01

**SARA 311/312 Hazards**

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

**Massachusetts Right To Know Components**

	CAS-No.	Revision Date
n-Hexane	110-54-3	2007-07-01

**Pennsylvania Right To Know Components**

	CAS-No.	Revision Date
n-Hexane	110-54-3	2007-07-01

**New Jersey Right To Know Components**

	CAS-No.	Revision Date
n-Hexane	110-54-3	2007-07-01

**California Prop. 65 Components**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

---

**16. OTHER INFORMATION****Further information**

Copyright 2011 Sigma-Aldrich Co. License granted to make unlimited paper copies for internal use only.  
The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Co., shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.